

# TH6-42

## CONSTRUCTION TELEHANDLERS



### Key Features

- ✓ SUPERVIEW cab design for increased line of sight to forks and load
- ✓ Simple F-N-R joystick mounted to the seat for ease of use and operator comfort
- ✓ EASY STEP cab floor allows for clear visibility of the step for exit and entry
- ✓ digital display with 50 operator aid messages to assist in correct operation
- ✓ No DEF or DPF systems
- ✓ high visibility orange seat belt to verify operator use
- ✓ stability system for machine re-position within restricted range.

### Key Specifications

- ✓ 6,000 lbs. (2722 kg) maximum lifting capacity
- ✓ 42' 6" (13 m) maximum lifting height
- ✓ 74 hp (55 kW) Deutz diesel engine

SPECIFICATIONS

IMPERIAL		
Capacities	Max. capacity	6000 lb
	Max. lifting height	42 ft 6 in
	Max. outreach	28 ft 6 in
Weight and dimensions	Overall length to carriage	20 ft 8 in
	Overall length (with forks)	24 ft 8 in
	Overall width	8 ft 2 in
	Overall height	8 ft
	Wheelbase	11 ft 6 in
	Ground clearance	1 ft 6 in
	Overall cab width	3 ft 1 in
	Tilt-up angle	34 °
	Tilt-down angle	96 °
	External turning radius	13 ft 1 in
	Overall weight	22851 lb
	Tires type	Pneumatic
Performances	Forks length / width / section	48 in x 4 in x 2 in
	Frame leveling longitudinal +/-	10 °
	Lifting	11 s
	Lowering	6 s
	Extension	17 s
	Retraction	11 s
Engine	Crowd	4 s
	Dump	6 s
	Engine brand	Deutz
	Engine norm	Tier 4 final
	Engine model	TCD 3.6 L4
	Number of cylinders / Capacity of cylinders	4 - 220 in³
Transmission	I.C. Engine power rating - Power	74 Hp / 55 kW
	Max. torque / Engine rotation	288 ft/lbs @ 2300 rpm
	Transmission type	Powershift
	Number of gears (forward / reverse)	5 / 3
	Max. travel speed	20 mph
	Parking brake	Hydraulic spring release SAHR
Hydraulics	Service brake	Wet disc brakes
	Hydraulic pump type	Axial piston
Tank capacities	Hydraulic flow / Pressure	40 US gpm-4000 PSI
	Engine oil	2 US gal
	Hydraulic oil	36 US gal
Noise and vibration	Fuel tank	38 US gal
	Noise at driving position (LpA)	80 dB
Miscellaneous	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2



STANDARD FEATURES

- Four Wheel Drive
- Crab mode
- Boom Tip Lift Hook
- Rear Axle Stabilization
- Wet disc brakes
- Back-Up Alarm
- Engine Block Heater
- 12Volt Power Port
- 12 Volt Battery
- Self-Leveling Forks
- Easy Manager
- Multi-Function Display Screen

OPTIONAL FEATURES

- A/C Cabin
- Suspension Seat
- Rock Tread - Air Foam Tires
- Cabin with Heat
- Work Lights - Front and Rear

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095  
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT